

Klemko Techniek B.V.  
Tel.: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

**Geïsoleerde Kabelschoen Waterdicht**

/productimages/130610.jpg

Package type: BX á 50 pce



**PRODUCT SPECIFICATIONS:**

Bolt dimension (metric)	3.5
Flange shape	Ring shape
Insulation	Polyethylene (PE)
Insulated	Yes
Colour insulation	Blue
Nominal cross section (mm <sup>2</sup> )	1.04 - 2.63
Reel/roll packaging	No
Sleeve form	Short
Colour	Blue
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine strand conductors	Yes
Suitable for high temperatures (to 650 °C)	No
Suitable for insulated varnish	No
Suitable for round conductors	Yes
Suitable for flat conductors	No
Temperature protected till (°C)	75
For pull protected connections	Yes
Material	Copper
Surface protection	Tinned
Max. current (I <sub>max</sub> ) (A)	30
Stud size (imperial)	Other
Halogen free	Yes
Total length (mm)	31
(mm)	5.5
(mm)	6.6
(mm)	31
Amperage (A)	27
(V)	600
Watertight	Yes
No	
No	
No	