

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl


klemko®

130640 - HSK2540GS

Geïsoleerde Kabelschoen Waterdicht

Package type: BX á 50 pce

/productimages/130640.jpg



PRODUCT SPECIFICATIONS:

Bolt dimension (metric)	4
Flange shape	Fork shape
Insulation	Polyethylene (PE)
Insulated	Yes
Colour insulation	Blue
Nominal cross section (mm ²)	1.04 - 2.63
Reel/roll packaging	No
Sleeve form	Short
Colour	Blue
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine strand conductors	Yes
Suitable for high temperatures (to 650 °C)	No
Suitable for insulated varnish	No
Suitable for round conductors	Yes
Suitable for flat conductors	No
Temperature protected till (°C)	75
For pull protected connections	Yes
Material	Copper
Surface protection	Tinned
Max. current (I _{max}) (A)	30
Stud size (imperial)	Other
Halogen free	Yes
Total length (mm)	33.5
(mm)	5.5
(mm)	7.2
(mm)	33.5
Amperage (A)	27
(V)	600
Watertight	Yes
Temperature (°C)	75
No	
No	
No	