

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

160110 - KCI-IP68-3/5P-6-14,5

160210.jpg

Package type: BG á 1 pce

PRODUCT SPECIFICATIONS:

| | |
|---|-------------------------|
| Contact type | Other |
| Diameter connector (mm) | 31 |
| Type of housing | Straight |
| Rated current In (A) | 24 |
| Ambient temperature (°C) | -20 - +110 |
| Rated voltage (V) | 450 |
| Connectable conductor cross section fine-strand without cable end sleeve (mm ²) | 0.2 - 2.5 |
| Connectable conductor cross section fine-strand with cable end sleeve (mm ²) | 0.2 - 2.5 |
| Connectable conductor cross section solid-core (mm ²) | 0.2 - 2.5 |
| Type of electric connection | Spring clamp connection |
| Material of contact surface | Brass |
| Housing material | Plastic |
| Locking mechanism | Gland nut |
| Inflammability class of insulation material according to with UL94 | V0 |
| With protective conductor | No |
| Degree of protection (IP), mounted | IP68 |
| Number of data contacts | 0 |
| Number of power contacts | 5 |
| Number of control contacts | 0 |
| For cable outer diameter (mm) | 6 - 14.5 |
| Material thread ring | Plastic |
| Screened | No |
| With status indication | No |