

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

611348 - LIN-24V-120IP67

liniLED Power

/productimages/611348.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	1 - 10 V
Model	Static
Output power (W)	1 - 120
Housing	Metal housing
Suitable for constant voltage	Yes
Output voltage (V)	24 - 24
Input voltage (V)	90 - 305
Suitable for DC-voltage (primary side)	No
Suitable for constant current	No
Degree of protection (IP)	IP67
Suitable for outdoor use	Yes
Length (mm)	196
Width (mm)	68
Height (mm)	39
Rated frequency (Hz)	50 - 60
Ambient temperature (°C)	-10 - +35
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Operation by Bluetooth	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Dimming 1-10 V	Yes
Dimming phase cut-on	No
Dimming DALI	No
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	No
No	