

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

Schemerschakelaar Opbouw

Package type: CT á 1 pce

/productimages/840005.jpg



PRODUCT SPECIFICATIONS:

Model	Surface mounting
Type of sensor	Built-in light sensor
Mounting method	Surface mounted (plaster)
Relay	
Colour	Grey
Engaging brightness (lx)	5 - 10000
Switching-off brightness (lx)	10 - 20000
Yes	
Switch-off delay (s)	60
Switching-on delay (s)	60
Contacts	1 make contact (NO)
Max. switching power (W)	2000
Max. switching power LED (W)	2000
Max. switching current (resistive load) (A)	8.7
(W)	1 - 2000
(W)	0.5
Suitable for C-load	Yes
With automatic night switch-off	No
Material	Plastic
Surface protection	Untreated
Surface finishing	Matt
Nominal voltage (V)	230
Voltage type	AC
Operating temperature (°C)	-25 - +45
Suitable for degree of protection (IP)	IP55
Width (mm)	74
Height (mm)	95
Depth (mm)	50
Swivelling	No
With DALI interface	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
Compatible with Apple HomeKit	No
IFTTT support available	No
Transparent	No