

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860051 - LD-4,2-7W700PD

Leddriver constante stroom

/productimages/860051.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Dynamic
Suitable for outdoor use	No
Housing	Plastic housing
Suitable for constant current	Yes
Suitable for constant voltage	No
Output voltage (V)	6 - 10
Output current (mA)	700 - 700
Suitable for DC-voltage (primary side)	No
Output power (W)	4.5 - 7
Degree of protection (IP)	IP20
Length (mm)	85
Width (mm)	40.4
Height (mm)	22
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DSI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming phase cut-off	Yes
Dimming phase cut-on	No
No	
Rated voltage (V)	220 - 240
Voltage type	DC
Rated frequency (Hz)	50 - 60
0.9	
Max. starting current (A)	1
(°C)	-25 - +85
White	
No	
2 - 3	
1 - 1	
Yes	
Yes	
Yes	
Operation by Bluetooth	No