

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860078 - LD-12-20W500PD

Leddriver constante stroom


/productimages/860078.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	Phase cut-off
Model	Dynamic
Output power (W)	12.5 - 21
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	25 - 42
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	500 - 500
No	
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	115
Width (mm)	41
Height (mm)	25
Rated frequency (Hz)	50 - 60
0.9	
Max. starting current (A)	16
Ambient temperature (°C)	-20 - +45
White	
No	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Dimming potentiometer (integrated)	No
Suitable for pulse button	No
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
(%)	10 - 100
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No



Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	Yes
Dimming 0-10 V	No