

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860080 - LA-DRV-18W500PD

Leddriver constante stroom

/productimages/860080.jpg

Package type: BG á 1 pce



PRODUCT SPECIFICATIONS:

Model	Dynamic
Output power (W)	9 - 18
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	18 - 36
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	500 - 500
No	
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	125
Width (mm)	53
Height (mm)	30
Rated frequency (Hz)	50 - 60
0.95	
Max. starting current (A)	5
Ambient temperature (°C)	-20 - +55
White	
No	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
(%)	10 - 100
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No

Dimming phase cut-off	No
Dimming 0-10 V	No
No	