

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860088 - LA-DRV-25W700PD

Leddriver constante stroom

/productimages/860088.jpg

Package type: BG á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	Phase cut-off
Output power (W)	12.6 - 25.2
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	18 - 36
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	700 - 700
No	
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	120
Width (mm)	45
Height (mm)	28
Rated frequency (Hz)	50 - 60
0.95	
Max. starting current (A)	5
Ambient temperature (°C)	-20 - +45
White	
No	
6 - 11	
2 - 3	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming LineSwitch	No
Dimming phase cut-on	No

Dimming DALI	No
Dimming programmable (%)	No
Dimming DMX	5 - 100
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	Yes
Dimming with push-button	No
No	No
Number of colour channels	1
DIN-rail mounting	No