

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 860095 - LB-LD-12V-12D

**Leddriver constante spanning**

/productimages/860095.jpg

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Protocol	Phase cut-off
Model	Static
Output power (W)	2.4 - 12
Housing	Plastic housing
Suitable for constant voltage	Yes
Output voltage (V)	12 - 12
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	Yes
Suitable for constant current	No
Output current (mA)	0.1 - 1
No	
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	50
Width (mm)	49
Height (mm)	24
0.95	
Max. starting current (A)	5
Ambient temperature (°C)	-20 - +50
White	
Yes	
Number of channels	1
(W)	12
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
Efficiency (%)	77
(kV)	0.5
None	
Max. number of luminaires per miniature circuit breaker B16	200
Max. number of luminaires per miniature circuit breaker C16	200
(h)	50000
Dimmable	Yes
PWM modulation	No



Operation by Bluetooth	No
Dimming DALI-2	No
IFTTT support available	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Compatible with Apple HomeKit	No
Suitable for pulse button	No
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	No
Dimming Sine Wave Reduction	No
Dimming DMX	No
Dimming mains voltage modulation	Yes
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	Yes
Dimming 0-10 V	No
Dimming with push-button	No
No	