

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860238 - LD-CC-ZV-MO-50

Leddriver constante stroom

/productimages/860238.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	Z-wave
Model	Dynamic
Suitable for outdoor use	No
Housing	Plastic housing
Suitable for constant current	Yes
Suitable for constant voltage	No
Output voltage (V)	8 - 48
Output current (mA)	250 - 1500
Suitable for DC-voltage (primary side)	No
Output power (W)	1 - 50
Degree of protection (IP)	IP20
Length (mm)	210
Width (mm)	50
Height (mm)	32
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DSI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Compatible with Casambi	No
Dimming Zigbee	No
Yes	
Rated voltage (V)	220 - 240
8 - 48	
Voltage type	DC
Rated frequency (Hz)	50 - 60
(°C)	-20 - +45
No	
No	
Yes	
Yes	
Yes	
Yes	



Operation by Bluetooth

No

