

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860269 - LD-24-PD-240

860190.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Protocol	Phase cut-off
Output power (W)	80 - 240
Power consumption (W)	21.6
Housing	Plastic housing
Suitable for constant voltage	Yes
Output voltage (V)	24 - 24
Voltage type	DC
Input voltage (V)	198 - 264
Suitable for DC-voltage (primary side)	Yes
Suitable for constant current	No
Output current (mA)	3.33 - 10
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	450
Width (mm)	32
Height (mm)	23
0.95	
Max. starting current (A)	65
Ambient temperature (°C)	-20 - +45
(%)	3
White	
No	
Number of channels	1
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Overtemperature protection	No
Yes	
Yes	
Short-circuit protected	Yes
No	
Efficiency (%)	91
(kV)	4
(kV)	2
None	
Max. number of luminaires per miniature circuit breaker B16	3
Max. number of luminaires per miniature circuit breaker C16	6
(h)	50000
Dimmable	Yes
Operation by Bluetooth	No

Dimming DALI-2	No
IFTTT support available	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Compatible with Apple HomeKit	No
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming LineSwitch	No
Dimming phase cut-on	Yes
Dimming DALI	No
Dimming programmable	No
Dimming Sine Wave Reduction (%)	1 - 100
Dimming DMX	No
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	Yes
Dimming 0-10 V	No
Dimming with push-button	No
No	
Number of colour channels	1
DIN-rail mounting	No