

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

860190.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

|   |                 |
|---|-----------------|
| Protocol                                  | DALI            |
| Model                                     | Static          |
| Output power (W)                          | 1 - 100         |
| Housing                                   | Plastic housing |
| Suitable for constant voltage             | Yes             |
| Output voltage (V)                        | 24 - 24         |
| Input voltage (V)                         | 220 - 240       |
| Suitable for DC-voltage (primary side)    | No              |
| Suitable for constant current             | No              |
| Degree of protection (IP)                 | IP20            |
| Protection class                          | II              |
| Suitable for outdoor use                  | No              |
| Length (mm)                               | 306.8           |
| Width (mm)                                | 43              |
| Height (mm)                               | 30              |
| Ambient temperature (°C)                  | -20 - +45       |
| White                                     |                 |
| No  |                 |
| Number of channels                        | 2               |
| Frequency input voltage (Hz)              | 50 - 60         |
| Independently operating                   | Yes             |
| Yes                                       |                 |
| Overload protection                       | Yes             |
| Yes                                       |                 |
| Overtemperature protection                | Yes             |
| Yes                                       |                 |
| Yes                                       |                 |
| Short-circuit protected                   | Yes             |
| No  |                 |
| None                                      |                 |
| Dimmable                                  | Yes             |
| Operation by Bluetooth                    | No              |
| Dimming DALI-2                            | Yes             |
| IFTTT support available                   | No              |
| Compatible with Google Assistant          | No              |
| Compatible with Amazon Alexa              | No              |
| Compatible with Casambi                   | No              |
| Dimming potentiometer (integrated)        | No              |
| Compatible with Apple HomeKit             | No              |
| Dimming RF                                | No              |
| Dimming manufacturer's proprietary system | No              |



|                                  |         |
|----------------------------------|---------|
| Dimming 1-10 V                   | No      |
| Dimming LineSwitch               | No      |
| Dimming phase cut-on             | No      |
| Dimming DALI                     | Yes     |
| Dimming programmable (%)         | Yes     |
|                                  | 1 - 100 |
| Dimming DMX                      | No      |
| Dimming mains voltage modulation | No      |
| Constant light output (CLO)      | No      |
| Dimming Touch and Dim            | No      |
| Dimming DSI                      | No      |
| Dimming Zigbee                   | No      |
| Dimming phase cut-off            | No      |
| Dimming 0-10 V                   | No      |
| Dimming with push-button         | Yes     |