

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

876804.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Protocol	Zigbee
Model	Dynamic
Output power (W)	1 - 10
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	6 - 28
Input voltage (V)	200 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	350 - 700
Yes	
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	103.7
Width (mm)	53
Height (mm)	30
Ambient temperature (°C)	-20 - +45
White	
No	
Number of channels	1
2 - 4	
1 - 3	
1 - 1	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming manufacturer's proprietary	No



system	
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	Yes
Dimming Sine Wave Reduction (%)	No
Dimming DMX	1 - 100
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	Yes
Dimming phase cut-off	No
Dimming 0-10 V	No
Dimming with push-button	No