

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863020 - BONNITA-40-EWW

Lumiko modulair spots

Package type: CT á 1 pce

/productimages/863020.jpg



PRODUCT SPECIFICATIONS:

| | |
|--|--------------------|
| Housing colour | Aluminium |
| Shape | Round |
| Operating current (mA) | 0 - 700 |
| Voltage type | DC |
| Lamp voltage (V) | 9.4 - 9.4 |
| Luminous flux (lm) | 0 - 530 |
| (lm) | 0 - 530 |
| Suitable for constant voltage | No |
| Suitable for constant current | Yes |
| External driver required | Yes |
| Colour temperature (K) | 2700 - 2700 |
| Number of LEDs | 1 |
| Colour | White |
| Connection type | Other |
| (cm) | 100 |
| Optics | Reflector |
| Diameter (mm) | 50 |
| Length (mm) | 50 |
| Width (mm) | 50 |
| Height (mm) | 62 |
| Built-in diameter (mm) | 50 |
| Degree of protection (IP) | IP20 |
| Energy efficiency class according to EU regulation 2019/2015 | F |
| Beam angle (°) | 40 - 40 |
| Lamp power (W) | 6.6 - 6.6 |
| Dimmable | Yes |
| Average nominal lifespan (h) | 50000 |
| Colour of light according to EN 12464-1 | Warm white <3300 K |
| Colour rendering index CRI | 80-89 |
| Colour consistency (McAdam ellipse) | SDCM1 |
| Specific luminous efficacy (lm/W) | 0 - 79 |
| Operating voltage (V) | 9.4 - 9.4 |
| IFTTT support available | No |
| Suitable for matrix information boards | No |
| Suitable for traffic lights | No |
| Suitable for rail traffic | No |
| Suitable for general lighting | Yes |
| Suitable for variable road signs | No |