

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863203 - DL-LUNA2W-NW

LED Downlighters

Package type: CT á 1 pce

/productimages/863203.jpg



PRODUCT SPECIFICATIONS:

Mounting method	Built-in
Colour temperature (K)	4000 - 4000
Suitable for lamp power (W)	1 - 26
Max. system power (W)	26
Nominal current (mA)	110 - 700
Nominal voltage (V)	36 - 36
Suitable for ceiling mounting	Yes
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP20
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	White
Rated luminous flux according to IEC 62722-2-1 (lm)	2200
Light sharing	Symmetric
Beam angle	Extreme wide beam >80°
Height/depth (mm)	134
Outer diameter (mm)	173
Built-in depth (mm)	107
Voltage type	DC
Colour of light	White
Colour rendering index CRI	80-89
Suitable for built-in mounting	Yes
Optics	Reflector
No	
(cm)	100
Built-in diameter (mm)	162 - 162
Number of poles	2
Emergency power supply integrated	No
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
Luminous flux adjustable	Continuously variable