

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863622 - LCB-IB-SM-WW

LED meubelspots

/productimages/863622.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Dimmable	Yes
Colour temperature (K)	3000 - 3000
Colour of light adjustable	No
Luminous flux (lm)	0 - 320
Rated luminous flux according to IEC 62722-2-1 (lm)	320
(lm/W)	0 - 103
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Voltage type	DC
Max. system power (W)	3.1
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Extreme wide beam >80°
Beam angle (°)	90
Built-in height (mm)	14
Length (mm)	48
Width (mm)	48
Height/depth (mm)	14
Outer diameter (mm)	48
Built-in width (mm)	39 - 40
Built-in diameter (mm)	37 - 40
Housing colour	Aluminium
Degree of protection (IP), front side	IP20
IP20	
Degree of protection (IP)	IP20
Suitable for ceiling mounting	Yes
Suitable for suspended mounting	No
Suitable for wall mounting	No
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3.1 - 3.1
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
Adjustability	not adjustable
With movement sensor	No
With light sensor	No
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled

With control gear	No
Colour of light	White
Housing material	Aluminium
Reflector	High-gloss
Light sharing	Symmetric
Colour rendering index CRI	90-100
Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
(cm)	100
Dimming potentiometer (integrated)	No
Light distributor	Reflector
Reflector colour	Silver
Light outlet	Direct
Number of poles	2
Connection type	Plug
Exchangeable control gear	Yes
Beam angle adjustable	No
Lamp power (W)	3.1
With presence indicator	No
None	
Dimming manufacturer's proprietary system	No
None	
IFTTT support available	No
Dimming Touch and Dim	No
(lm)	0 - 320