

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/863641.jpg


Led spots. inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	2700 - 2700
Colour of light adjustable	No
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Voltage type	DC
Max. system power (W)	3.1
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Medium beam 21-40°
Beam angle (°)	40
Built-in depth (mm)	27
Height/depth (mm)	27
Outer diameter (mm)	50
Built-in diameter (mm)	45 - 48
Housing colour	Aluminium
Degree of protection (IP), front side	IP44
Other	
Suitable for ceiling mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3.1 - 3.1
Suitable for clamp-mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Reflector
Material cover	Glass transparent
(cm)	100
Light distributor	Diffuser lens/optic/panel
Reflector colour	Silver
Light outlet	Direct

On the left side of the page, there are five horizontal bars of different colors: orange, blue, light green, and grey, stacked vertically.

Number of poles	2
Connection type	Push-in clamp
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
Beam angle adjustable	No
With mounting bracket	No
With presence indicator	No
Dimmable	Yes