

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863685 - LCB-OPB-ZW-EWW

Led spots, opbouw

/productimages/863685.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Surface mounting
Colour temperature (K)	2700 - 2700
Luminous flux (lm)	10 - 320
Suitable for lamp power (W)	3.1 - 3.1
Max. system power (W)	3.1
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Suitable for ceiling mounting	Yes
Suitable for pedestal/floor mounting	Yes
Adjustability	Swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP44
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	Black
Moulded-on	
Rated luminous flux according to IEC 62722-2-1 (lm)	320
Light sharing	Symmetric
Beam angle	Medium beam 21-40°
Width (mm)	36
Beam angle (°)	40
Height/depth (mm)	45
Outer diameter (mm)	32
Voltage type	DC
Colour of light	White
Colour rendering index CRI	80-89
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Optics	Reflector
(cm)	100
Light distributor	Reflector
Light outlet	Direct
Number of poles	2
Emergency power supply integrated	No
Suitable for wall mounting	Yes
Exchangeable control gear	Yes
Luminous flux adjustable	Continuously variable
Beam angle adjustable	No



With mounting bracket Yes



Energy efficiency class of the light source according to EU regulation 2019/2015 E

