

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863695 - LCB-SP-SLIM-NW

Led spots, inbouw

/productimages/863695.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Dimmable	Yes
Colour temperature (K)	4000 - 4000
Colour of light adjustable	No
(lm)	0 - 320
(lm/W)	0 - 103
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Voltage type	DC
Max. system power (W)	3.1
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Extreme wide beam >80°
Beam angle (°)	90
Built-in height (mm)	13.7 - 13.7
Height/depth (mm)	13.7
Outer diameter (mm)	65
Built-in diameter (mm)	61 - 61
Housing colour	Aluminium
Degree of protection (IP), front side	IP44
Other	
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3.1 - 3.1
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
(cm)	200
Light distributor	Diffuser lens/optic/panel
Light outlet	Direct
Number of poles	2
Exchangeable control gear	Yes
Beam angle adjustable	No
With presence indicator	No