

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 863696 - LCB-SP-SLIM-WW

Led spots, inbouw

/productimages/863696.jpg

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

|  |   |
|--|---|
| Spot   |   |
| Mounting method  | Built-in                                |
| Dimmable   | Yes                                     |
| Colour temperature (K)   | 3000 - 3000                             |
| Colour of light adjustable   | No                                      |
| (lm)   | 0 - 320                                 |
| (lm/W)   | 0 - 103                                 |
| Nominal current (mA)   | 0 - 350                                 |
| Nominal voltage (V)  | 8.8 - 8.8                               |
| Voltage type   | DC                                      |
| Max. system power (W)  | 3.1                                     |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | E                                       |
| Beam angle   | Extreme wide beam >80°                  |
| Beam angle (°)   | 90                                      |
| Built-in height (mm)   | 13.7 - 13.7                             |
| Height/depth (mm)  | 13.7                                    |
| Outer diameter (mm)  | 65                                      |
| Built-in diameter (mm)   | 61 - 61                                 |
| Housing colour   | Aluminium                               |
| Degree of protection (IP), front side  | IP44                                    |
| Other  |   |
| Luminous flux adjustable   | Continuously variable                   |
| Suitable for lamp power (W)  | 3.1 - 3.1                               |
| Adjustability  | not adjustable                          |
| Lamp type  | LED not exchangeable                    |
| With light source  | Yes                                     |
| Electrical connection with connector system                                      | Yes                                     |
| Type of control gear   | LED operating device current-controlled |
| With control gear  | No                                      |
| Colour of light  | White                                   |
| Housing material   | Aluminium                               |
| Light sharing  | Symmetric                               |
| Colour rendering index CRI   | 80-89                                   |
| Suitable for surface mounting  | Yes                                     |
| Suitable for built-in mounting   | Yes                                     |
| (cm)   | 200                                     |
| Light distributor  | Diffuser lens/optic/panel               |
| Light outlet   | Direct                                  |
| Number of poles  | 2                                       |
| Exchangeable control gear  | Yes                                     |
| Beam angle adjustable  | No                                      |
| With presence indicator  | No                                      |