

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863720 - LCB-SPOT-62RB-WW

Led spots, inbouw

/productimages/863720.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	3000 - 3000
Luminous flux (lm)	0 - 320
Suitable for lamp power (W)	3.1 - 3.1
Max. system power (W)	3.1
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Suitable for ceiling mounting	Yes
Suitable for clamp-mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP44
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	Stainless steel
Rated luminous flux according to IEC 62722-2-1 (lm)	320
Light sharing	Symmetric
Beam angle	Medium beam 21-40°
Beam angle (°)	40
Height/depth (mm)	27
Outer diameter (mm)	62
Built-in depth (mm)	27
Voltage type	DC
Colour of light	White
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Reflector
(cm)	100
Light distributor	Reflector
Light outlet	Direct
Built-in height/depth (mm)	27
Built-in diameter (mm)	50 - 50
Number of poles	2
Emergency power supply integrated	No
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
Luminous flux adjustable	Continuously variable

Beam angle adjustable	No
With mounting bracket	No
Energy efficiency class of the light source according to EU regulation 2019/2015	E