

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863778 - LCB-SIB-PA-W-WW

Led spots, inbouw

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Dimmable	Yes
Colour temperature (K)	3000 - 3000
Colour of light adjustable	No
Luminous flux (lm)	0 - 415
Rated luminous flux according to IEC 62722-2-1 (lm)	415
(lm)	0 - 415
(lm/W)	0 - 133
Nominal current (mA)	0 - 350
Nominal voltage (V)	8.8 - 8.8
Voltage type	DC
Max. system power (W)	3.1
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Beam angle	Medium beam 21-40°
Beam angle (°)	35
Built-in height (mm)	88 - 84
Length (mm)	60
Width (mm)	30
Height/depth (mm)	89
Outer diameter (mm)	54
Built-in diameter (mm)	49 - 50
Housing colour	White
Degree of protection (IP), front side	IP20
IP20	
Degree of protection (IP)	IP20
Suitable for ceiling mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3.1 - 3.1
Suitable for clamp-mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes

Optics (cm)	Lens
Light distributor	100
Light outlet	Focal lens
Number of poles	Direct
Colour consistency (McAdam ellipse)	2
Exchangeable control gear	SDCM1
Beam angle adjustable	Yes
With presence indicator	No
None	No
Dimming manufacturer's proprietary system	No
None	