

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/863852.jpg


Led spots. inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Dimmable	Yes
Colour temperature (K)	3000 - 3000
Colour of light adjustable	No
(lm)	0 - 320
(lm/W)	0 - 103
Nominal current (mA)	0 - 350
Nominal voltage (V)	9.2 - 9.2
Voltage type	DC
Max. system power (W)	3.3
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Medium beam 21-40°
Beam angle (°)	40
Height/depth (mm)	27
Outer diameter (mm)	50
Built-in diameter (mm)	45 - 48
Housing colour	Aluminium
Degree of protection (IP), front side	IP44
Other	
Suitable for ceiling mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3.1 - 3.3
Suitable for clamp-mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Reflector
Material cover	Glass transparent
Light distributor	Diffuser lens/optic/panel
Reflector colour	Silver

On the left side of the page, there are five horizontal bars of different colors: orange, blue, light green, and grey. The blue bar is the most prominent.

Light outlet	Direct
Number of poles	2
Connection type	Plug
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
Beam angle adjustable	No
With mounting bracket	No
With presence indicator	No