

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/864405.jpg

SP90 armaturen

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

| | |
|---|---|
| Colour of light | White |
| Suitable for suspended mounting | Yes |
| Suitable for ceiling mounting | Yes |
| Suitable for wall mounting | No |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Lamp type | LED not exchangeable |
| With light source | Yes |
| Type of control gear | LED operating device current-controlled |
| With control gear | Yes |
| Nominal voltage (V) | 36 - 36 |
| (V) | 220 - 240 |
| Nominal current (mA) | 700 - 700 |
| Colour temperature (K) | 3500 - 3500 |
| Housing material | Aluminium |
| Housing colour | White |
| Suitable for light line configuration | Yes |
| Material cover | Plastic, opal |
| Light sharing | Symmetric |
| Beam angle | Extreme wide beam >80° |
| Light outlet | Direct |
| Length (mm) | 1200 |
| Width (mm) | 90 |
| Height/depth (mm) | 30 |
| With movement sensor | No |
| With light sensor | No |
| Max. system power (W) | 24 |
| Voltage type | DC |
| Colour rendering index CRI | 80-89 |
| Suitable for lamp power (W) | 24 - 24 |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (%) | 70 |
| Dimmable | Yes |
| With presence indicator | No |
| IP20 | |
| Degree of protection (IP), front side | IP20 |
| None | |
| With switch | No |