

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/864455.jpg

**SP90 armaturen**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

|   |   |
|---|---|
| Colour of light   | White                                   |
| Suitable for suspended mounting   | Yes                                     |
| Suitable for ceiling mounting   | Yes                                     |
| Suitable for wall mounting  | No                                      |
| Suitable for built-in mounting  | No                                      |
| Suitable for surface mounting   | Yes                                     |
| Lamp type   | LED not exchangeable                    |
| With light source   | Yes                                     |
| Type of control gear  | LED operating device current-controlled |
| With control gear   | No                                      |
| Nominal voltage (V)   | 36 - 36                                 |
| (V)   | 220 - 240                               |
| Nominal current (mA)  | 100 - 700                               |
| Colour temperature (K)  | 3500 - 3500                             |
| Housing material  | Aluminium                               |
| Housing colour  | White                                   |
| Suitable for light line configuration   | Yes                                     |
| Material cover  | Plastic, opal                           |
| Light sharing   | Symmetric                               |
| Beam angle  | Extreme wide beam >80°                  |
| Light outlet  | Direct                                  |
| Length (mm)   | 1200                                    |
| Width (mm)  | 90                                      |
| Height/depth (mm)   | 30                                      |
| With movement sensor  | No                                      |
| With light sensor   | No                                      |
| Max. system power (W)   | 24                                      |
| Voltage type  | DC                                      |
| Colour rendering index CRI  | 80-89                                   |
| Suitable for lamp power (W)   | 24 - 24                                 |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (%) | 70                                      |
| Dimmable  | Yes                                     |
| With presence indicator   | No                                      |
| IP20  |   |
| Degree of protection (IP), front side   | IP20                                    |
| None  |   |
| With switch   | No                                      |