

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 864475 - SP90-172MT-NWW-DA

SP90 armaturen

/productimages/864475.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Colour of light	White
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
Lamp type	LED not exchangeable
With light source	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Nominal voltage (V)	54 - 54
(V)	220 - 240
Nominal current (mA)	700 - 700
Colour temperature (K)	3500 - 3500
Housing material	Aluminium
Housing colour	White
Suitable for light line configuration	Yes
Material cover	Plastic, opal
Light sharing	Symmetric
Beam angle	Extreme wide beam >80°
Light outlet	Direct
Length (mm)	1720
Width (mm)	90
Height/depth (mm)	18
Built-in length (mm)	1710
Built-in width (mm)	95
Built-in height/depth (mm)	18
With movement sensor	No
With light sensor	No
Max. system power (W)	36
Voltage type	DC
Colour rendering index CRI	80-89
Dimming DALI	Yes
Suitable for lamp power (W)	36 - 36
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (%)	70
Dimmable	Yes
With presence indicator	No
IP20	
Degree of protection (IP), front side	IP20
None	
With switch	No