

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

864510 - LA-IOB-PIR-CCT8-13

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Colour of light	White
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for wall mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Suitable for emergency lighting	No
Nominal voltage (V)	220 - 240
Colour temperature (K)	2700 - 400
Housing material	Plastic
Housing colour	White
Suitable for light line configuration	No
Material cover	Plastic, opal
Light sharing	Symmetric
Beam angle	Extreme wide beam >80°
Light outlet	Direct
Length (mm)	240
Width (mm)	240
Height/depth (mm)	20
Outer diameter (mm)	240
Built-in height/depth (mm)	20
With movement sensor	Yes
With light sensor	Yes
Protection class	II
Covering of the luminaire with thermally insulating material possible	Yes
Max. system power (W)	13
Voltage type	AC
Colour rendering index CRI	80-89
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No

Dimming programmable	Yes
Dimming RF	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
Operation by Bluetooth	No
Light distributor	Diffuser lens/optic/panel
Colour consistency (McAdam ellipse)	SDCM6
Degree of protection (NEMA)	2
Suitable for lamp power (W)	8 - 13
Type of wiring	Ending
Number of poles	2
Connection type	Cable
Exchangeable control gear	No
Dimming DALI-2	No
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (%)	96
Colour of light adjustable	Positions
Beam angle adjustable	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Compatible with Casambi	No
Passive infrared	
Dimmable	No
(lm/W)	97.5 - 101
(lm)	720 - 1286
With presence indicator	Yes
IP20	
Degree of protection (IP), front side	IP20
None	
None	
Suitable for clamp-mounting	Yes
With mounting material	Yes
With switch	No