

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

868103 - LM-BTSP-7W-15NW

Lumiko modulair B-trackspots

Package type: CT á 1 pce

/productimages/868103.jpg



PRODUCT SPECIFICATIONS:

Colour temperature (K)	4000 - 4000
Colour of light adjustable	No
Nominal voltage (V)	230 - 230
Voltage type	AC
Max. system power (W)	6.9
(lm)	0 - 650
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Narrow beam 11 - 20°
Beam angle (°)	15
Length (mm)	60
Width (mm)	94
Height/depth (mm)	106
(mm)	44
Outer diameter (mm)	44
Housing colour	Black
Degree of protection (IP), front side	IP20
IP20	
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	6.9 - 6.9
Suitable for light-track mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	90-100
Optics	Lens
Suitable for low voltage cable system	No
Yes	
Surface protection	Powder coating
Surface brushed	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming phase cut-on	No
Light distributor	Focal lens

Light outlet	Direct
Number of poles	3
Connection type	Busbar adapter
Colour consistency (McAdam ellipse)	SDCM2
With mounting bracket	No
With presence indicator	No
Dimming manufacturer's proprietary system	No
Dimmable	Yes
Dimming phase cut-off	Yes
Dimming 0-10 V	No
Dimming DMX	No
Dimming DALI-2	No