

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

868172 - LM-WBTSP26W-30WW

Lumiko modulair B-trackspots

Package type: CT á 1 pce

/productimages/868172.jpg



PRODUCT SPECIFICATIONS:

| | |
|--|---|
| Colour temperature (K) | 3000 - 3000 |
| Colour of light adjustable | No |
| Nominal current (mA) | 0 - 700 |
| Nominal voltage (V) | 230 - 230 |
| Voltage type | AC |
| Max. system power (W) | 26 |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | E |
| Beam angle | Medium beam 21-40° |
| Beam angle (°) | 30 |
| Length (mm) | 107 |
| Width (mm) | 148 |
| Height/depth (mm) | 140 |
| (mm) | 90 |
| Outer diameter (mm) | 90 |
| Housing colour | White |
| Degree of protection (IP), front side | IPX0 |
| IP20 | |
| Suitable for lamp power (W) | 26 - 26 |
| Suitable for light-track mounting | Yes |
| Adjustability | Rotating and swivelling |
| Lamp type | LED not exchangeable |
| With light source | Yes |
| Electrical connection with connector system | Yes |
| Type of control gear | LED operating device current-controlled |
| With control gear | Yes |
| Colour of light | White |
| Housing material | Aluminium |
| Light sharing | Symmetric |
| Colour rendering index CRI | 90-100 |
| Optics | Lens |
| Suitable for low voltage cable system | No |
| Yes | |
| Surface protection | Powder coating |
| Surface brushed | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming phase cut-on | No |
| Light distributor | Focal lens |
| Light outlet | Direct |

| | |
|---|----------------|
| Number of poles | 3 |
| Connection type | Busbar adapter |
| Colour consistency (McAdam ellipse) | SDCM2 |
| With mounting bracket | No |
| With presence indicator | No |
| Dimming manufacturer's proprietary system | No |
| Dimmable | Yes |
| Dimming phase cut-off | Yes |
| Dimming 0-10 V | No |
| Dimming DMX | No |
| Dimming DALI-2 | No |