

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

868315 - LM-EG18-UGR-NW

Lumiko modulair downlighters

Package type: CT á 1 pce

/productimages/868315.jpg



PRODUCT SPECIFICATIONS:

Housing colour	Aluminium
Shape	Round
Operating current (mA)	110 - 500
Voltage type	DC
Lamp voltage (V)	36 - 36
Luminous flux (lm)	0 - 1850
(lm)	0 - 1850
Suitable for constant voltage	No
Suitable for constant current	Yes
External driver required	Yes
Colour temperature (K)	4000 - 4000
Number of LEDs	1
Colour	White
Connection type	Other
(cm)	50
Optics	Reflector
Diameter (mm)	145
Length (mm)	145
Width (mm)	145
Height (mm)	125
Built-in diameter (mm)	123
Degree of protection (IP)	IP20
Energy efficiency class according to EU regulation 2019/2015	E
Beam angle (°)	90 - 90
Lamp power (W)	18.4 - 18.4
Dimmable	Yes
Average nominal lifespan (h)	50000
Colour of light according to EN 12464-1	Neutral white 3300-5300 K
Colour rendering index CRI	80-89
Colour consistency (McAdam ellipse)	SDCM1
Specific luminous efficacy (lm/W)	0 - 103
Operating voltage (V)	36 - 36
IFTTT support available	No
Suitable for matrix information boards	No
Suitable for traffic lights	No
Suitable for rail traffic	No
Suitable for general lighting	Yes
Suitable for variable road signs	No