

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 870004 - P300-DUO-PROF

**Bewegingsmelder Opbouw**

Package type: CT á 1 pce

/productimages/870004.jpg



**PRODUCT SPECIFICATIONS:**

Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP55
Response value luminosity (lx)	10 - 2000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	Yes
With remote control	No
(mm)	150
Width (mm)	80
Height (mm)	84
Max. mounting height (m)	5
Max. reach sideways (m)	16
15	
Diameter reach on floor (m)	16
(m)	20
(W)	2300
(VA)	400
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
(VA)	1000
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Other
Surface finishing	Matt
Voltage type	AC
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	15 - 300
Nominal voltage (V)	220 - 240
Max. switching power (W)	2300
Max. presence range (m <sup>2</sup> )	900
2	
Scan angle (°)	300
(W)	0.5
Connection type	Screwed terminal



Frequency (Hz)	50 - 60
Suitable for ceiling mounting	Yes
Suitable for wall mounting	Yes
Suitable for wireless transmission	No
Forced switch off	No
With connection cable	No
Yes	
Yes	
(A)	10
(m <sup>2</sup> )	680
(m <sup>2</sup> )	900
10 - 2000	
Yes	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
No	
Yes	
Transparent	No
IFTTT support available	No