

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 870050 - WATCHER-150

Bewegingsmelder opbouw

Package type: CT á 1 pce

/productimages/870050.jpg



**PRODUCT SPECIFICATIONS:**

Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP55
Response value luminosity (lx)	10 - 10000
HVAC-control	Yes
Optimum mounting height (m)	2
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
(mm)	119.5
Width (mm)	73.5
Height (mm)	87.5
Depth (mm)	119.5
Max. mounting height (m)	5
Max. reach sideways (m)	6
2	
Diameter reach on floor (m)	12
(m)	20
(W)	1000
(VA)	150
(W)	150
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Other
Surface finishing	Matt
Voltage type	AC
Max. starting current (A)	78
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Pivoting range sensor, horizontal (°)	0 - 90
Pivoting range sensor, vertical (°)	0 - 130
Nominal voltage (V)	220 - 240
Max. switching power (W)	1000
Max. switching power LED (W)	150



Max. presence range (m <sup>2</sup> )	300
Scan angle (°)	180
(W)	0.5
Connection type	Screwed terminal
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	Yes
Suitable for wall mounting	Yes
Suitable for wireless transmission	No
Forced switch off	No
With connection cable	No
Yes	
Yes	
(m <sup>2</sup> )	120
(m <sup>2</sup> )	300
No	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
With alarm function	No
No	
Yes	
Transparent	No
IFTTT support available	No