

Klemko Techniek B.V.  
Tel.: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870052.jpg

**Bewegingsmelder opbouw**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Forced switch off	No
Relay	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	2
Max. reach sideways (m)	6
(VA)	100
Diameter reach on floor (m)	12
(W)	100
Suitable for wireless transmission	No
Remote operation	No
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	1000
Mounting method	Surface mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Other
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP65
Voltage type	AC/DC
Min. switch-on time (s)	5
(mm)	119.5
Max. duty cycle (min)	12
Detection angle horizontal (°)	1 - 180
Pivoting range sensor, horizontal (°)	0 - 90
Pivoting range sensor, vertical (°)	0 - 130
Response value luminosity (lx)	10 - 10000
No	
Max. switching power (W)	1000
(W)	0.5
Number of switching zones	1



Max. starting current (A)	78
Frequency (Hz)	50 - 60
With alarm function	No
Scan angle (°)	180
Max. presence range (m <sup>2</sup> )	300
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No
Width (mm)	73.5
Height (mm)	87.5
Depth (mm)	119.5
Max. switching power LED (W)	100
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	11 - 32
No	
(m)	20
(m <sup>2</sup> )	120
(m <sup>2</sup> )	300
No	
No	
Compatible with Casambi	No