

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870060.jpg

## Bewegingsmelder Opbouw

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Passive infrared/ultrasonic (dual)	
Constant light control	No
HVAC-control	Yes
Forced switch off	No
Relay	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	2.5
Max. reach sideways (m)	16
(VA)	400
Diameter reach on floor (m)	16
(W)	400
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	2300
Mounting method	Surface mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Halogen free	No
Surface protection	Other
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP55
Voltage type	AC
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	0 - 240
Pivoting range sensor, horizontal (°)	90 - 90
Pivoting range sensor, vertical (°)	40 - 90
Response value luminosity (lx)	5 - 10000
Max. switching power (W)	2300
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	240
Max. presence range (m <sup>2</sup> )	800

## 870060 - PIR-HF 240 DUO

---



Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No
Width (mm)	80
Height (mm)	99
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
Yes	
(m)	20
(m <sup>2</sup> )	530
(m <sup>2</sup> )	800
No	
No	
Compatible with Casambi	No