

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 870464 - HB-PIR-UNI 15M

/productimages/870464.jpg

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Ceiling	
Degree of protection (IP)	IP55
HVAC-control	No
Optimum mounting height (m)	15
Model	Movement sensor
Constant light control	No
No	
Remote operation	Yes
With remote control	No
Width (mm)	105
Height (mm)	62.5
Diameter (mm)	105
Built-in depth (mm)	43.5
Built-in diameter (mm)	68
Max. mounting height (m)	15
Diameter reach on floor (m)	20
(m)	20
(VA)	800
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Voltage type	AC
Nominal voltage (V)	220 - 240
(st)	10
Max. presence range (m <sup>2</sup> )	320
Scan angle (°)	360
Connection type	Screwed terminal
Frequency (Hz)	50 - 60
Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Teach-function for response value luminosity	Yes
With connection cable	No
Yes	
(m <sup>2</sup> )	320
Yes	

Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
Animal zone	No
Transparent	No
IFTTT support available	No
Anti-bacterial treatment	No