

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870470.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP20
Response value luminosity (lx)	10 - 2000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
Width (mm)	80
Height (mm)	5
Diameter (mm)	80
(mm)	65
Built-in depth (mm)	67
Built-in diameter (mm)	63
Built-in size (mm)	63
Max. mounting height (m)	4
Max. reach sideways (m)	3.5
Max. reach frontally (m)	2
25	
Diameter reach on floor (m)	7
(W)	2000
(VA)	800
(W)	600
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
Bridging switch	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9016
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Matt
Voltage type	AC
Max. starting current (A)	800

Min. switch-on time (s)	30
Max. duty cycle (min)	30
Detection angle horizontal (°)	5 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	2000
Max. switching power LED (W)	600
Max. presence range (m ²)	50
6	
Scan angle (°)	360
Connection type	Screwed terminal
Substation input	No
Frequency (Hz)	50 - 60
No	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Forced switch off	No
Teach-function for response value luminosity	Yes
With connection cable	No
Yes	
Yes	
Yes	
Ambient temperature (°C)	-10 - +40
Dim function with dimmer basic element	No
Networkable	No
Compatible with Apple HomeKit	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
With alarm function	No
No	
Animal zone	No
Transparent	No
IFTTT support available	No
Anti-bacterial treatment	No