

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 870476 - PLF-OPB-PIR-UNI9-ZW

Aanwezigheidsdetector Universeel

Package type: CT á 1 pce

/productimages/870476.jpg



## PRODUCT SPECIFICATIONS:

Ceiling	
Degree of protection (IP)	IP55
Response value luminosity (lx)	10 - 2000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	Yes
With remote control	No
Width (mm)	105
Height (mm)	48
Diameter (mm)	105
(mm)	65
Built-in depth (mm)	43.5
Built-in diameter (mm)	68
Built-in size (mm)	68
Max. mounting height (m)	3
Max. reach sideways (m)	4.5
Max. reach frontally (m)	2.5
Diameter reach on floor (m)	9
(m)	12
(VA)	800
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
Response value luminosity adjustable	Yes
Colour	Black
RAL-number (similar)	9005
Material	Plastic
Material quality	Thermoplastic
Voltage type	AC
Max. starting current (A)	800
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Detection angle horizontal (°)	5 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	2300
Max. switching power LED (W)	600
Max. presence range (m <sup>2</sup> )	65
6	
Scan angle (°)	360
Connection type	Screw terminal

Frequency (Hz)	50 - 60
Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Teach-function for response value luminosity	Yes
With connection cable	No
Yes	
Yes	
(m <sup>2</sup> )	65
(m <sup>2</sup> )	113
Yes	
Yes	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Apple HomeKit	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
Animal zone	No
Transparent	No
IFTTT support available	No
Anti-bacterial treatment	No