

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

870560.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	5
(VA)	600
Max. reach frontally (m)	2
Diameter reach on floor (m)	10
(W)	400
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	2300
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Mounting method	Surface mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Matt
Colour	White
RAL-number (similar)	9016
Transparent	No
Degree of protection (IP)	IP55
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
No	
Detection angle horizontal (°)	60 - 360
Response value luminosity (lx)	10 - 2000
Max. switching power (W)	2300
Number of switching zones	1
Max. starting current (A)	117



Substation input	Yes
Frequency (Hz)	50 - 60
With alarm function	No
Scan angle (°)	360
Max. presence range (m <sup>2</sup> )	154
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No
Anti-bacterial treatment	No
Width (mm)	111.7
Height (mm)	39.9
Diameter (mm)	111.7
Max. switching power LED (W)	400
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	220 - 240
Yes	
6	
No	
No	
Compatible with Casambi	No