

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 870543 - IB-PIR-W-55x55

Bewegingsmelder inbouw

870540.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	No
Forced switch off	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	1.2
Staircase monitoring	No
Bridging switch	Yes
Max. reach sideways (m)	8
(VA)	600
Diameter reach on floor (m)	8
(W)	400
Suitable for wireless transmission	No
Remote operation	No
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	2000
With signal unit	No
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	1.5
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Glossy
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP20
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Response value luminosity (lx)	10 - 1000
No	
Max. switching power (W)	2000

Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	180
Suitable for ceiling mounting	No
Connection type	Push-in clamp
With connection cable	No
Width (mm)	80
Height (mm)	80
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
1 make contact (NO)	
Yes	
Yes	
6	
(st)	6
5 - 1000	
Yes	
No	
No	
Compatible with Casambi	No