

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

**Bewegingsmelder inbouw**

Package type: CT á 1 pce

/productimages/870544.jpg



## PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP40
Response value luminosity (lx)	5 - 2000
HVAC-control	No
Optimum mounting height (m)	1.2
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
(mm)	80
Width (mm)	80
Height (mm)	80
Depth (mm)	24
Built-in length (mm)	55
Built-in width (mm)	55
Built-in depth (mm)	32
Max. mounting height (m)	1.5
Max. reach sideways (m)	8
Diameter reach on floor (m)	8
(W)	300
(VA)	100
(W)	100
Number of switching zones	1
Passive infrared	
Integrated	
Staircase monitoring	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
With signal unit	No
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Glossy
Voltage type	AC
Max. starting current (A)	80
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Nominal voltage (V)	220 - 240
Max. switching power (W)	300



Max. switching power LED (W)	100
2	
Scan angle (°)	180
(W)	0.7
Connection type	Screwed terminal
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	No
Suitable for wall mounting	Yes
Suitable for wireless transmission	No
Forced switch off	Yes
Teach-function for response value luminosity	Yes
With connection cable	No
Yes	
1 make contact (NO)	
No	
Yes	
No	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
With alarm function	No
No	
Animal zone	No
Transparent	No
IFTTT support available	No