

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870545 - IB-PIR-W/LED-ZW

Bewegingsmelder inbouw

870540.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Model	Movement sensor
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	No
Forced switch off	Yes
Animal zone	No
Integrated	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	1.2
Staircase monitoring	No
Max. reach sideways (m)	7
(VA)	100
Diameter reach on floor (m)	7
(W)	100
Suitable for wireless transmission	No
Remote operation	No
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	300
With signal unit	No
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	1.5
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Matt
Colour	Black
RAL-number (similar)	9005
Transparent	No
Degree of protection (IP)	IP40
Voltage type	AC
Min. switch-on time (s)	5
(mm)	80
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Response value luminosity (lx)	5 - 2000
Max. switching power (W)	300
(W)	0.7
Number of switching zones	1



Max. starting current (A)	80
Frequency (Hz)	50 - 60
With alarm function	No
Scan angle (°)	180
Suitable for ceiling mounting	No
Connection type	Screwed terminal
With connection cable	No
Width (mm)	80
Height (mm)	80
Depth (mm)	24
Built-in width (mm)	55
Built-in depth (mm)	32
Built-in length (mm)	55
Max. switching power LED (W)	100
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
1 make contact (NO)	
No	
2	
Yes	
No	
No	
Compatible with Casambi	No