

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870546 - IB-PIR-W/10MG

Bewegingsmelder inbouw

/productimages/870546.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Movement sensor
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	No
Forced switch off	Yes
Animal zone	No
Integrated	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	1.2
Staircase monitoring	No
Max. reach sideways (m)	9
(VA)	500
Diameter reach on floor (m)	8
Suitable for wireless transmission	No
Remote operation	No
10	
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
With signal unit	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	1.5
Material	Plastic
Material quality	Thermoplastic
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP40
Voltage type	AC
Min. switch-on time (s)	1
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 200
(mm)	35
Response value luminosity (lx)	5 - 10000
Max. switching power (W)	2000
(W)	1
Number of switching zones	1
Max. starting current (A)	350
Frequency (Hz)	50 - 60
Scan angle (°)	200
Suitable for ceiling mounting	No
Connection type	Screwed terminal

With connection cable	No
Width (mm)	80
Height (mm)	80
Depth (mm)	24
Built-in width (mm)	50
Built-in depth (mm)	32
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
1 make contact (NO)	
Yes	
10	
No	
No	
Compatible with Casambi	No