

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

Bewegingsmelder inbouw

Package type: CT á 1 pce

/productimages/870547.jpg



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP40
Response value luminosity (lx)	5 - 10000
HVAC-control	No
Optimum mounting height (m)	1.2
Model	Movement sensor
Constant light control	No
No	
Remote operation	Yes
With remote control	No
Max. reach sideways (m)	8
10	
Diameter reach on floor (m)	16
(VA)	500
Number of switching zones	1
Passive infrared	
Integrated	
Staircase monitoring	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
With signal unit	No
Colour	White
RAL-number (similar)	1013
Material	Plastic
Material quality	Thermoplastic
Voltage type	AC
Max. starting current (A)	350
Min. switch-on time (s)	1
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 200
Nominal voltage (V)	220 - 240
Max. switching power (W)	2000
10	
Scan angle (°)	200
(W)	1
Connection type	Screwed terminal
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	No
Suitable for wall mounting	Yes
Suitable for wireless transmission	No
Forced switch off	Yes
With connection cable	No

Yes

1 make contact (NO)

No

Dim function with dimmer basic element No

Networkable No

Compatible with Casambi No

Compatible with Google Assistant No

Compatible with Amazon Alexa No

No

Animal zone No

Transparent No

IFTTT support available No