

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870550.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

| | |
|---------------------------------------|-------------------------|
| Mounting method | Flush mounted (plaster) |
| Ceiling | |
| Degree of protection (IP) | IP44 |
| Response value luminosity (lx) | 10 - 2000 |
| HVAC-control | Yes |
| Optimum mounting height (m) | 2.5 |
| Model | Movement sensor |
| Constant light control | No |
| Yes | |
| Remote operation | Yes |
| With remote control | No |
| (mm) | 135 |
| Width (mm) | 80 |
| Height (mm) | 15 |
| Diameter (mm) | 80 |
| (mm) | 54 |
| Built-in depth (mm) | 38 |
| Built-in diameter (mm) | 65 |
| Built-in size (mm) | 65 |
| Length of connection cable (mm) | 1 |
| Max. mounting height (m) | 5 |
| Max. reach sideways (m) | 4 |
| 25 | |
| Diameter reach on floor (m) | 7 |
| (W) | 2000 |
| (VA) | 800 |
| Number of switching zones | 1 |
| Passive infrared | |
| RJ12 | |
| Relay | |
| Response value sensitivity adjustable | Yes |
| Response value luminosity adjustable | Yes |
| Colour | White |
| RAL-number (similar) | 9010 |
| Material | Plastic |
| Material quality | Thermoplastic |
| Surface protection | Lacquered |
| Surface finishing | Matt |
| Voltage type | AC |
| Min. switch-on time (s) | 10 |
| Max. duty cycle (min) | 60 |
| Detection angle horizontal (°) | 30 - 360 |



| | |
|--|------------------|
| Nominal voltage (V) | 220 - 240 |
| Max. switching power (W) | 2000 |
| (st) | 5 |
| Max. presence range (m ²) | 165 |
| Scan angle (°) | 360 |
| (W) | 1.2 |
| Connection type | Screwed terminal |
| Frequency (Hz) | 50 - 60 |
| Suitable for ceiling mounting | Yes |
| Suitable for wall mounting | No |
| Suitable for wireless transmission | No |
| Forced switch off | No |
| With connection cable | No |
| Yes | |
| Yes | |
| (A) | 10 |
| Yes | |
| Yes | |
| Ambient temperature (°C) | 0 - 45 |
| Dim function with dimmer basic element | No |
| Networkable | No |
| Compatible with Casambi | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| No | |
| No | |
| Transparent | No |
| IFTTT support available | No |