

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870555.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP20
Response value luminosity (lx)	10 - 2000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Other
Constant light control	No
Yes	
Remote operation	Yes
With remote control	No
Width (mm)	80
Height (mm)	15
Diameter (mm)	80
(mm)	50
Built-in depth (mm)	38
Built-in diameter (mm)	65
Built-in size (mm)	65
Length of connection cable (mm)	10
Max. mounting height (m)	5
Diameter reach on floor (m)	7
Number of switching zones	1
Passive infrared	
RJ12	
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Detection angle horizontal (°)	1 - 360
(st)	5
Max. presence range (m ²)	165
Scan angle (°)	360
Connection type	Other
Suitable for wall mounting	No
Suitable for wireless transmission	No
With connection cable	Yes
Yes	
Yes	
Dim function with dimmer basic element	No
Networkable	No



No
Compatible with Casambi No
Compatible with Google Assistant No
Compatible with Amazon Alexa No



No
Transparent No
IFTTT support available No

