

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870557.jpg

Aanwezigheidsdetector Universeel

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Ceiling	
Degree of protection (IP)	IP44
Response value luminosity (lx)	5 - 10000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
(mm)	26
Built-in diameter (mm)	65
Built-in size (mm)	65
Max. mounting height (m)	5
Max. reach sideways (m)	3
10	
Diameter reach on floor (m)	7
(m)	8
(W)	2000
(VA)	500
(W)	400
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
(VA)	900
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Max. starting current (A)	10
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	2200
Max. presence range (m ²)	50



2	
Scan angle (°)	360
(W)	0.8
Connection type	Screw terminal
Suitable for C-load	Yes
Frequency (Hz)	50 - 60
Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Forced switch off	No
With connection cable	No
Yes	
1 make contact (NO)	
Yes	
(m ²)	40
(m ²)	50
Yes	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
No	
Transparent	No
IFTTT support available	No