

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870575.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP40
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Other
Constant light control	No
Yes	
Remote operation	Yes
With remote control	No
Width (mm)	80
Height (mm)	16
Diameter (mm)	80
Built-in depth (mm)	38
Built-in diameter (mm)	65
Built-in size (mm)	65
(m)	10
Max. mounting height (m)	5
Diameter reach on floor (m)	6
Number of switching zones	1
Passive infrared	
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Detection angle horizontal (°)	1 - 360
(st)	2
Max. presence range (m ²)	50
Scan angle (°)	360
Connection type	Other
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
With connection cable	Yes
Yes	
Yes	
Dim function with dimmer basic element	No
Networkable	No
Yes	
Compatible with Casambi	No

Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
Transparent	No
IFTTT support available	No