

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870620 - PLF-UNI-PIR30-D2

Aanwezigheidsdetector Plafond Inbouw

/productimages/870620.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Ceiling	
Degree of protection (IP)	IP44
Response value luminosity (lx)	10 - 2000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	Yes
Yes	
Remote operation	Yes
With remote control	No
Width (mm)	110
Height (mm)	75
Diameter (mm)	110
Built-in depth (mm)	47
Built-in diameter (mm)	65
Built-in size (mm)	65
Max. mounting height (m)	3
Max. reach sideways (m)	15
15	
Diameter reach on floor (m)	30
(m)	30
(W)	2300
Control current (mA)	5
(VA)	500
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
(VA)	1000
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Max. starting current (A)	350
Min. switch-on time (s)	1
Max. duty cycle (min)	60
Detection angle horizontal (°)	1 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	2200



(st)	10
Max. presence range (m ²)	700
Scan angle (°)	360
(W)	1
Connection type	Screwed terminal
Frequency (Hz)	50 - 50
Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Forced switch off	No
With connection cable	No
Yes	
Yes	
(m ²)	700
(m ²)	700
Yes	
Dim function with dimmer basic element	Yes
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Yes	
No	
Transparent	No
IFTTT support available	No