

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870620 - PLF-UNI-PIR30-D2

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce

/productimages/870620.jpg



PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	Yes
HVAC-control	Yes
Forced switch off	No
Relay	
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	15
(VA)	500
Diameter reach on floor (m)	30
Suitable for wireless transmission	No
Remote operation	Yes
15	
With remote control	No
(VA)	1000
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
(W)	2300
Max. mounting height (m)	3
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP44
Voltage type	AC
Min. switch-on time (s)	1
Max. duty cycle (min)	60
Yes	
Detection angle horizontal (°)	1 - 360
Response value luminosity (lx)	10 - 2000
Yes	
Max. switching power (W)	2200
(W)	1
Built-in size (mm)	65
Number of switching zones	1
Max. starting current (A)	350
Control current (mA)	5
Frequency (Hz)	50 - 50



Scan angle (°)	360
Max. presence range (m ²)	700
Suitable for ceiling mounting	Yes
Connection type	Screw terminal
With connection cable	No
Width (mm)	110
Height (mm)	75
Diameter (mm)	110
Built-in depth (mm)	47
Built-in diameter (mm)	65
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	230 - 230
Yes	
(m)	30
(m ²)	700
(m ²)	700
(st)	10
No	
Yes	
Compatible with Casambi	No